

Lighting Your Life Since 1970

Product Specifications - 20031SWSN		
Job Name:	Job Type:	
Quantity:	Comments	



20031SWSN

Deven 3-Light Semi Flush

Finis	sh
Satin	Nickel

Lamping

Number of Bulbs 3 **Light Type** Incandescent **Bulb Type** MB Max Bulb Wattage 60 Max Fixture Wattage 180 Rated Life **Rated Lumens** ±0 Color Temp Not Included Bulb(s) Light Up/Down **Beam Spread** N/A N/A **Photo Cell Included** N/A Ballast/Driver/Transformer No Dimmable N/A

Glass/Shade

Satin White

Measurements

Width 14.00" Height 10.00" Length N/A Extension N/A **Back Plate Width** N/A **Back Plate Height** N/A **HCO** N/A Min Overall Height 0.00" Max Overall Height N/A **Hanging Weight** 3.63 lbs Height Adjustable N/A Slope N/A **Chain Length** N/A Wire Length N/A **Canopy Width** N/A **Canopy Height** N/A **Canopy Length** N/A

Product Category

Semi-Flush Mount

Chinning

Snipping	
Carton Weight	5.50 lbs
Carton Width	15"
Carton Height	10"
Carton Length	15"
Carton Cubic Feet	1.31
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Cartification

Certification		Otner
Safety Rating	Dry	UPC (
Energy Star	No	Shade
CA Title 24	No	Cryst
CA Title 20	No	Diffus
ADA	No	Conv
Dark Sky	N/A	Mater

Other	
UPC Code	783209101388
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	N/A

Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.