


Lighting Your Life Since 1970

Product Specifications - 25104FTSN		
Job Name:	Job Type:	
Quantity:	Comments	



25104FTSN

Hi-Bay 1-Light Pendant



Finish

Satin Nickel

Glass/Shade

Frosted

Product Category

Single Pendant

Lamping

Number of Bulbs	1
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	100
Max Fixture Wattage	100
Rated Life	±2,500 Hours
Rated Lumens	±1,150
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

weasurements	
Width	14.25"
Height	23.50"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	0.00"
Max Overall Height	67.50"
Hanging Weight	9.46 lbs
Height Adjustable	N/A
Slope	120°
Chain Length	N/A
Wire Length	72"
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Shipping

Jilippilig	
Carton Weight	11.66 lbs
Carton Width	15"
Carton Height	19"
Carton Length	15"
Carton Cubic Feet	2.32
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

Certification	Other	
Safety Rating	Dry UPC Cod	le
Energy Star	No Shades I	ncluded
CA Title 24	No Crystals	Included
CA Title 20	No Diffuser	Included
ADA	No Convers	ion Kit
Dark Sky	N/A Material	

Equivalents

783209093768

N/A

N/A

N/A

N/A Metal

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.