


Lighting Your Life Since 1970

Product Specifications - 39754FTMS		
Job Name:	Job Type:	
Quantity:	Comments	



39754FTMS

Pinnacle LED 18-Light Pendant



Finish Metallic Silver

wetanic Silve

Lamping

Number of Bulbs	18
Light Type	LED
Bulb Type	LED
Max Bulb Wattage	2.5
Max Fixture Wattage	45
Rated Life	
Rated Lumens	±0
Color Temp	±3,000 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	Yes
Dimmable	Standard/Lutron® or Leviton® CL

Glass/Shade

Frosted

Measurements

Canopy Length

Othor

Width 19.00" Height 19.75" Length 38.00" Extension N/A Back Plate Width N/A **Back Plate Height** N/A HCO N/A Min Overall Height 0.00" Max Overall Height 60.00" **Hanging Weight** 26.10 lbs Height Adjustable N/A Slope N/A **Chain Length** N/A Wire Length N/A **Canopy Width** N/A Canopy Height N/A

Product Category

Single-Tier Chandelier

Shipping

Carton Weight	31.68 lbs
Carton Width	23"
Carton Height	17"
Carton Length	42"
Carton Cubic Feet	9.33
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

Ceruncation	Other	
Safety Rating	Dry UPC Code	
Energy Star	No Shades Included	
CA Title 24	No Crystals Included	
CA Title 20	No Diffuser Included	
ADA	No Conversion Kit	
Dark Sky	N/A Material	

Equivalents

N/A

N/A N/A N/A N/A

783209111332

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.