

## Lighting Your Life Since 1970

Product Specifications - 5827CLSN			
Job Name:	Job Type:		
Quantity:	Comments		



## **5827CLSN Essentials 2-Light Flush Mount**



**Finish** Satin Nickel

Lamping

Lamping	
Number of Bulbs	2
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	60
Max Fixture Wattage	120
Rated Life	±2,500 Hours
Rated Lumens	±1,344
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

G	lass	/Sh	ad	le

Measurements Width

Back Plate Width

**Back Plate Height** 

Min Overall Height

Max Overall Height

**Hanging Weight** 

Chain Length

**Canopy Width** 

**Canopy Height** 

**Canopy Length** 

Wire Length

Height Adjustable

Clear

Height

Length

HCO

Slope

Extension

Product	Category
Flush Mo	unt
Flush Mo	unt

91	٦i	n	ni	n	a
SI	ш	Μ	μι	ш	У

13.50"

6.00"

N/A

0.00"

2.65 lbs

Snipping	
Carton Weight	4.08 lbs
Carton Width	14"
Carton Height	6"
Carton Length	14"
Carton Cubic Feet	0.63
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Cortification Othor

Certification		Other	
Safety Rating	Dry	UPC Code	783209582781
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	Iron

## **Equivalents**

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.