


Lighting Your Life Since 1970

Product Specifications - 5882CLWT	
Job Name:	Job Type:
Quantity:	Comments



5882CLWT **Essentials 1-Light Flush Mount**



Finish White

Lamping

=ampmg	
Number of Bulbs	1
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	60
Max Fixture Wattage	60
Rated Life	±2,500 Hours
Rated Lumens	±672
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

G	lass	Sh	aa	le

Clear

IV	easurements
W	idth .

Width	7.50'
Height	4.50'
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
НСО	N/A
Min Overall Height	0.00'
Max Overall Height	4.50'
Hanging Weight	1.65 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Product Category

Flush Mount

Shippina

Shipping	
Carton Weight	1.98 lbs
Carton Width	8"
Carton Height	7"
Carton Length	8"
Carton Cubic Feet	0.26
Master Pack	8
Master Pack Weight	16.89 lbs
Master Pack Width	17.13"
Master Pack Height	13.58"
Master Pack Length	17.13"
Master Cubic Feet	2.31
UPS Shippable	Yes

Certification

Safety Rating Dry **Energy Star** No CA Title 24 No CA Title 20 No **ADA** No Dark Sky N/A

Other	
UPC Code	783209588219
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	Iror

Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.