

Lighting Your Life Since 1970

Product Specifications - 6204FTWT		
Job Name:	Job Type:	
Quantity:	Comments	



6204FTWT

Outdoor Essentials 2-Light Outdoor Ceiling Mount

Finish Glass/Shade **Product Category Outdoor Ceiling Mount** White Frosted

Number of Bulbs	2
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	75
Max Fixture Wattage	150
Rated Life	±2,500 Hours
Rated Lumens	±1,600
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard Dimmer

Measurements

measurements	
Width	9.50"
Height	5.00"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	3.00 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Shinning

Silippilig	
Carton Weight	4.00 lbs
Carton Width	11'
Carton Height	7
Carton Length	11'
Carton Cubic Feet	0.48
Master Pack	3
Master Pack Weight	36.00 lbs
Master Pack Width	22.13
Master Pack Height	15.38
Master Pack Length	22.38
Master Cubic Feet	4.41
UPS Shippable	Yes

Cartification

Certification		Other	
Safety Rating	Damp	UPC Code	783209620438
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	Steel

Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.