


## Lighting Your Life Since 1970

Product Specifications - 7000601			
Job Name:	Job Type:		
Quantity:	Comments		



70006OI Loft 9-Light Chandelier



Oil Rubbed Bronze

Lamping

Number of Bulbs	
Light Type	
Bulb Type	
Max Bulb Wattage	
May Fixture Wattage	

60 540 Rated Life ±1,500 Hours **Rated Lumens** ±6,048 **Color Temp** ±2,700 K Bulb(s) Not Included Light Up/Down N/A Beam Spread N/A N/A **Photo Cell Included** N/A Ballast/Driver/Transformer No Dimmable Standard Dimmer

Glass/Shade

9

CA

Incandescent

ПΛ	Δ:	20	11	ro	m	nt	c

Width	29.50"
Height	29.00"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	10.71 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	72"
Wire Length	180"
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

**Product Category** 

Multi-Tier Chandelier

Shinning

Jilippilig	
Carton Weight	17.64 lbs
Carton Width	30"
Carton Height	7"
Carton Length	32"
Carton Cubic Feet	3.65
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification		0
Safety Rating	Dry	U
Energy Star	No	S
CA Title 24	No	С
CA Title 20	No	D
ADA	No	C
Dark Sky	N/A	M

Other	
UPC Code	783209014497
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	Iror

**Equivalents** 

Incandescent Watts N/A	A
Fluorescent Watts N/A	Α

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.