

Lighting Your Life Since 1970

Product Specifications - 85885MROI		
Job Name:	Job Type:	
Quantity:	Comments	



85885MROI **Essentials EE 2-Light Flush Mount**



Finish Oil Rubbed Bronze

Lamping

Number of Bulbs	2
Light Type	Fluorescent
Bulb Type	GU24
Max Bulb Wattage	13
Max Fixture Wattage	26
Rated Life	±10,000 Hours
Rated Lumens	±1,800
Color Temp	±2,700 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	81-82
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	No

Glass/Shade
Marble

Measurements	s

Width	9.00"
Height	5.00"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
НСО	N/A
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	2.20 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Product Category

Flush Mount

0	L	*	-	٠	

Shipping	
Carton Weight	2.87 lbs
Carton Width	11"
Carton Height	6"
Carton Length	11"
Carton Cubic Feet	0.48
Master Pack	8
Master Pack Weight	29.23 lbs
Master Pack Width	23.62"
Master Pack Height	13.78"
Master Pack Length	23.62"
Master Cubic Feet	4.45
UPS Shippable	Yes

Certification

o or arroadorr		
Safety Rating	Dry	UF
Energy Star	Yes	Sh
CA Title 24	Yes	Cr
CA Title 20	No	Di
ADA	No	Co
Dark Sky	N/A	Ma

Other	
UPC Code	783209086487
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	N/A

Equivalents

Incandescent Watts	164
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.