

## Lighting Your Life Since 1970

Product Specifications - 92007WT			
Job Name:	Job Type:		
Quantity:	Comments		



## 92007WT Outdoor Essentials 1-Light Outdoor Wall Mount

Finish Glass/Shade White

Product Category
Outdoor Wall Mount

Lamping	
Number of Bulbs	1
Light Type	Incandescent
Bulb Type	PAR38
Max Bulb Wattage	75
Max Fixture Wattage	75
Rated Life	±750 Hours
Rated Lumens	±2,175
Color Temp	±2,500 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

Measurements	
Width	5.50"
Height	10.50"
Length	N/A
Extension	10"
Back Plate Width	5.00"
Back Plate Height	5.00"
HCO	3.00"
Min Overall Height	0.00"
Max Overall Height	10.50"
Hanging Weight	1.20 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Shipping	
Carton Weight	1.80 lbs
Carton Width	6'
Carton Height	11'
Carton Length	6'
Carton Cubic Feet	0.24
Master Pack	6
Master Pack Weight	11.00 lbs
Master Pack Width	13.00'
Master Pack Height	12.13'
Master Pack Length	19.13'
Master Cubic Feet	1.75
UPS Shippable	Yes

Certification		Other		Equiv
Safety Rating	Wet	UPC Code	783209012707	Incan
Energy Star	No	Shades Included	N/A	Fluore
CA Title 24	No	Crystals Included	N/A	
CA Title 20	No	Diffuser Included	N/A	
ADA	No	Conversion Kit	N/A	
Dark Sky	N/A	Material	Die Cast Aluminum	

Equivalents	
Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.