Radar | E21464-WTBK Job Name:______Job Type:_____Quantity:_____Comments:







PRODUCT DESCRIPTION

Soft ambient light is cast indirectly off the contoured white reflector by LED cleverly concealed in the Black cup centered on the disc. Light can be directed by adjusting the gimbaled reflector.

1.5" [134.25" | 134.25"

ø16.5"

max overall height

MEASUREMENTS

DIMENSION : 16.5" L x 16.5" W x 12.75" H

MAX OAH : 134.25" OAH

CANOPY : 5" W x 1.25" H x 5" L

HANGING WEIGHT : 4.48 lb

LAMPING

INPUT VOLTAGE : 120V

LUMENS : 525 Rated (280 Del.)

BULB : 1 x 7.5W LED PCB Integrated, 8W Total

BULB INCLUDED : (Integrated)
DIMMABLE : Triac CL or ELV
CRI : 90+ CRI

CRI : 90+ CRI COLOR_TEMP : 3000K

FINISHES OPTION

White / Black

MATERIAL

Polycarbonate, Aluminum

RATINGS

cETLus Dry Location



ADDITIONAL

ADJUSTABLE SLOPE: 30 RATED LIFE 50000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.

