

Job Type:

## **PRODUCT DESCRIPTION**

A collection of very small LED pendants unique to the market. Shades of Gypsum, Concrete, and Aluminum available in a wide variety of shapes and finishes, these small scale pendants provide an amazing amount of light. The light engine is housed in machined aluminum to reduce heat. Drivers recess into the outlet box so the canopies are very low profile in keeping with the small scale of the pendant.



## **MEASUREMENTS**

BULB

CRI

DIMMABLE

DIMENSION		: 3.25"
MAX OAH		: 122"
CANOPY		: 5" W
HANGING WEIGHT		: 1.22
LAMPING		
INPUT VOLTAGE	:	100-240V
LUMENS	:	412 Rate
BIIIB		1 v / 8W

"L x 3.25" W x 2.75" H OAH x 0.5" H x 5" L lb / ed (212 Del.) : 1 x 4.8W LED PCB Integrated , 6W Total : (Integrated)

- **BULB INCLUDED** : Triac CL or ELV
  - : 90+ CRI
- COLOR\_TEMP : 3000K

## FINISHES OPTION



MATERIAL Aluminum, Polycarbonate

RATINGS Dry Location



## ADDITIONAL

ADJUSTABLE SLOPE: 70 RATED LIFE 25000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Comments: