

iBAR | FRIENDS OF HUE


E35020 | E35022

- Friends of HUE product
- Aluminum Construction with Clear Acrylic diffuser
- Available in Brushed Aluminum with black accents or Brushed Black with chrome accents
- Dimmable only with Hue compatible devices
- Color Ambience tuning
- CRI 90+
- Unlock all the features with Philips HUE Bridge
Compatible with Amazon Echo, Apple HomeKit, Google Home, and other Smart Home Controls

Job Name : _____
 Job Type : _____
 Quantity : _____
 Comments : _____



LEMSC19001
 Phillip Hue Bridge
 (NOT included ~ Available for purchase)



PRODUCT DESCRIPTION

The iBar Friends of Hue collection features aluminum channels anodized in your choice of Brushed Aluminum or Brushed Black. The pendants support a solid block of Clear acrylic which creates a dramatic lighting effect. Entertain with 96 million color combinations or enjoy the health benefits of a regularly changing color temperature to suit the mood of the day. With Philips Hue technology, you can program a variety of themes for the ultimate in convenience, health, security, and entertainment.

MEASUREMENTS

MODEL	DIMENSION	CANOPY	WIRE LENGTH
E35020	41.75"L x 4.75"W x 6"H, 124.75"OAH	23.5"L x 4.75"W x 1.75"H	120"L
E35022	61.50"L x 4.75"W x 6"H, 124.75"OAH	23.5"L x 4.75"W x 1.75"H	120"L

LAMPING

MODEL	BULB TYPE	CRI	LUMENS		INPUT
			RATED	DEL	
E35020	30W PCB LED (Integrated)	80+	2100	1680	120-277V
E35022	40W PCB LED (Integrated)	80+	2800	2100	120-277V

- Dimmable only with Hue compatible devices.
- Requires Philips Hue Bridge for smart control or Philips Hue Wireless Dimmer Switch (not included)
- Unlock all features with a Philips Hue Bridge. Learn more on meethue.com

Always consult a qualified electrician before installing any lighting product

FINISHES OPTIONS:

- Brushed Black (BBK)
- Aluminum (AL)



MATERIAL:

Aluminum + Steel + Acrylic

SHADE MATERIAL:

Acrylic

RATINGS:

- cETLus
- Dry location
- Friends of Hue
- Dimmable (with Phillip Hue Compatible device)



ADDITIONAL:

- SLOPE: 70
- RATED LIFE: 50,000 hrs
- OPERATING TEMP: -20° C (-4°), 40° C (104°F)