

ALUMILUX™ I SUSPENSION

E41467 | E41468


- ETL, cETL IP65
- LED 3000K, CRI 90+, ELV Dimming
- Available in 4' and 5' Lengths
- Available in Satin Aluminum (SA) and White (WT)
- Title 24 JA8 Listed
- Dry Location

Job Name : _____
 Job Type : _____
 Quantity : _____
 Comments : _____



PRODUCT DESCRIPTION

Available in various shapes and colors, this collection of pendants provide a full range of streamlined, architectural design. Cast and extruded pieces of aluminum provide illumination that complement the sleek styling of commercial applications and minimalist modern design. Be it over a table or a work station, these versatile products direct lighting for both task and decorative uses.



MEASUREMENT

MODEL	DIMENSION	CANOPY	HANGING WEIGHT	MAX OH	MIN OH
E41467*	46.75"L x 4.5"W x 2.75"H	17.75"L x 4.25"W x 1"H	7.57 LB	122.5"	4.5"
E41468	58.25"L x 4.5"W x 2.75"H	17.75"L x 4.25"W x 2.75"H	8.80 LB	122.5"	4.5"

LAMPING

MODEL	BULB TYPE	CRI	LUMENS	COL TEMP.	DIMMABLE	INPUT
E41467*	(2)15W LED (Integrated), 30W Total	90+	2100	3000K	ELV	120V
E41468	(2)17.5W LED (Integrated), 35W Total	90+	2450	3000K	ELV	120V

* E41467 - Only available in Satin Aluminum (SA)

FINISHES OPTIONS:

- White (WT)
- Satin Aluminum (SA)



MATERIAL:

Aluminum + Acrylic

AVAILABLE SIZES:

46.75" / 58.25"

RATINGS:

ETL cETL
 Dry Location
 Title 24 JA8



ADDITIONAL:

RATED LIFE: 40,000 Hours
 OPERATING TEMP: -20° C (-4°), 40° C (104° F)
 PHOTOMETRIC: Report Found Online

Always consult a qualified electrician before installing any lighting product