

ALUMILUX™ I WALL SCONCE

E41485 | E41486 | E41488

- ETL/cETL IP65
- LED 3000K, CRI 90+
- Wet Location
- Title 24 for outdoor use

Job Name : _____
 Job Type : _____
 Quantity : _____
 Comments : _____



E41485




E41486



E41488

PRODUCT DESCRIPTION

Bring the outdoors inside with our line of Architectural high quality interior and exterior wall sconces. European in design and machined out of blocks of solid Aluminum, these sconces have both the look and quality expected for the discriminate buyer. High powered LEDs create dramatic light effects and most are approved for wet location applications.



E41485

MEASUREMENT

MODEL	DIMENSION	HCO	HANGING WEIGHT	BP WIDTH	BP HEIGHT
E41485	7.88"W x 5.7"H x 3.9"EXT	5.00"	2.20 LB	4"	4"
E41486	7.88"W x 5.1"H x 2.4"EXT	4.70"	2.42 LB	4"	4"
E41488	23.64"W x 5.1"H x 2.4"EXT	12.00"	7.07 LB	4"	4"



E41486

LAMPING

MODEL	BULB TYPE	CRI	LUMENS	COL TEMP.	DIMMABLE	INPUT
E41485	(1) 18W PCB LED (Integrated)	90+	560	3000K	ELV	120V
E41486	(1) 16W PCB LED (Integrated)	90+	1120	3000K	ELV	120V
E41488	(1) 30W PCB LED (Integrated)	90+	2100	3000K	ELV	120V



E41488

FINISHES OPTIONS:

- Bronze (BZ)
- Satin Aluminum (SA)
- White (WT)



MATERIAL:

Aluminum

AVAILABLE MODELS:

E41485 | E41486 | E41488

RATINGS:

- ETL cETL IP65
- Wet Location
- ADA
- Title 24 (For Outdoor use)



ADDITIONAL:

- RATED LIFE: 40,000 Hours
- OPERATING TEMP: -20° C (-4°), 40° C (104° F)
- PHOTOMETRIC: Report Found Online
- LIGHTING DIRECTION: Indirect
- INSTALL DIRECTION: Horizontal/ Vertical

Always consult a qualified electrician before installing any lighting product