

ALUMILUX | WALL SCONCE

E41524 | E41526


- ETL/cETL IP65
- LED 3000K, CRI 90+
- Wet Location
- Title 24 for outdoor use
- Dimmable with ELV Dimmer

Job Name : _____
 Job Type : _____
 Quantity : _____
 Comments : _____




PRODUCT DESCRIPTION

Bring the outdoors inside with our line of Architectural high quality interior and exterior wall sconces. European in design and machined out of blocks of solid Aluminum, these sconces have both the look and quality expected for the discriminate buyer. High powered LEDs create dramatic light effects and most are approved for wet location applications.



E41524



E41526

MEASUREMENT

MODEL	DIMENSION	HANGING WEIGHT	HCO	BP WIDTH	BP HEIGHT
E41524	4.25"W x 13.75"H x 3.5"EXT	3.74 LB	11.75"	4.35"	4.35"
E41526	4.25"W x 23.5"H x 3.5"EXT	4.62 LB	11.75"	4.35"	4.35"

LAMPING

MODEL	BULB TYPE	CRI	LUMENS	COL TEMP.	DIMMABLE	INPUT
E41524	(1) 4W PCB LED (Integrated)	90+	560	3000K	ELV	120V
E41526	(2) 4W PCB LED (Integrated)	90+	560	3000K	ELV	120V

FINISHES OPTIONS:

- White (WT)
- Bronze (BZ)



MATERIAL:

Aluminum + Acrylic

AVAILABLE MODELS:

E41524 | E41526

RATINGS:

ETL cETL IP65
 Wet Location
 Title 24 (For Outdoor Use)
 ADA



ADDITIONAL:

RATED LIFE: 50,000 Hours
 OPERATING TEMP: -20° C (-4°), 40°C (104°F)
 PHOTOMETRIC: Report Found Online
 INSTALL DIRECT: Horizontal/ Vertical
 LIGHT DIRECTION: Up/ Down

Always consult a qualified electrician before installing any lighting product