# ALUMI**LUX** I WALL SCONCE

# E41524 | E41526

- ETL/cETL IP65
- LED 3000K, CRI 90+
- Wet Location
- Title 24 for outdoor use
- Dimmable with ELV Dimmer







Job Name: \_\_\_ Job Type : \_\_\_\_\_ Quantity: Comments:

#### **PRODUCT DESCRIPTION**

Bring the outdoors inside with our line of Architectural high quality interior and exterior wall sconces. European in design and machined out of blocks of solid Aluminum, these sconces have both the look and quality expected for the discriminate buyer. High powered LEDs create dramatic light effects and most are approved for wet location applications.





## **MEASUREMENT**

MODEL	DIMENSION	WEIGHT	нсо	BP WIDTH	BP HEIGHT
E41524	4.25"W x 13.75"H x 3.5"EXT	3.74 LB	11.75"	4.35"	4.35"
E41526	4.25"W x 23.5"H x 3.5"EXT	4.62 LB	11.75"	4.35"	4.35"

HANGING

#### LAMPING

MODEL	BULB TYPE	CRI	LUMENS	TEMP.	DIMMABLE	INPUT
E41524	(1) 4W PCB LED (Integrated)	90+	560	3000K	ELV	120V
E41526	(2) 4W PCB LED (Integrated)	90+	560	3000K	ELV	120V

COL

Always consult a qualified electrician before installing any lighting product

#### FINISHES OPTIONS:

White (WT) Bronze (BZ)



#### MATERIAL:

Aluminum + Acrylic

#### **AVAILABLE MODELS:**

E41524 | E41526

#### **RATINGS:**

ETL cETL IP65 Wet Location Title 24 (For Outdoor Use) ADA









### **ADDITIONAL:**

RATED LIFE: 50,000 Hours OPERATING TEMP: -20° C (-4°), 40°C (104°F) PHOTOMETRIC: Report Found Online INSTALL DIRECT: Horizontal/ Vertical LIGHT DIRECTION: Up/ Down

