

Product	Specifications	for	F22563-	81PC

Ŀ	Job Name:	Job Type:				
ŀ						
ď	Quantity:	Comments				
1						
П						



E22563-81PC

Zing 4-Light RapidJack Pendant and Canopy

N/A

Finish Glass/Shade **Product Category** Polished Chrome Multi-Light Pendant Mirror Chrome

Canopy Length

Lamping		Measurements	
Number of Bulb(s)	4	Width	12.00"
Light Type	LED	Height	N/A
Bulb Type	LED	Length	N/A
Max Bulb Wattage	3	Extension	N/A
Max Fixture Wattage	12	Back Plate Width	N/A
Rated Life	N/A	Back Plate Height	N/A
Rated Lumens	±600	HCO	N/A
Color Temp	N/A	Min Overall Height	N/A
Bulb(s) Included	Yes	Max Overall Height	134.00"

N/A

N/A N/A

N/A

No Low-Voltage

Electronic Dimmer

Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	134.00"
Hanging Weight	N/A
Height Adjustable	Yes
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A

Shipping	
Carton Weight	N/A
Carton Width	N/A
Carton Height	N/A
Carton Length	N/A
Carton Cubic Feet	N/A
Master Pack	N/A
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

C	_	 	-	_	4	•	_	

Ballast/Driver/Transformer

Light Up/Down

Photo Cell Included

Beam Spread

Dimmable

Certification		Other		Equivalents
Safety Rating	Dry	UPC Code	845094071549	Incandescen
Energy Star	No	Material	N/A	Fluorescent \
CA Title 24	No			
CA Title 20	No			
ADA	No			

Incandescent Watts	N/A
Fluorescent Watts	N/A

ET2 Contemporary Lighting and all designs, logos and images © 2014 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.