

ntemporary	Job Name:
ghting™	Quantity:
	_

E23140-10PC

Product Specifications for E23140-10PC

Comments

Spiral 1-Light Pendant

Finish Polished Chrome

Lamping Number of Bulb(s) **Light Type** Xenon **Bulb Type** G9 Max Bulb Wattage 60 Max Fixture Wattage 60 **Rated Life** ±2,000 Hours **Rated Lumens** ±800 **Color Temp** ±2,900 K Bulb(s) Included Yes Light Up/Down **Beam Spread** N/A N/A **Photo Cell Included** N/A Ballast/Driver/Transformer No Dimmable Standard

Glass/Shade

Wire Length

Other

UPC Code

Material

Canopy Width

Canopy Height

Canopy Length

Measurements Width 6.00" Height 11.75" Length N/A Extension N/A **Back Plate Width** N/A **Back Plate Height** N/A HCO N/A Min Overall Height N/A **Max Overall Height** 130.00" Hanging Weight 2.75 lb(s) **Height Adjustable** Yes Slope 120° Chain Length N/A

Product Category Single Pendant

Shipping	
Carton Weight	3.96 lb(s)
Carton Width	8.66'
Carton Height	13.19'
Carton Length	8.66'
Carton Cubic Feet	N/A
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes
	Carton Weight Carton Width Carton Height Carton Length Carton Cubic Feet Master Pack Master Pack Weight Master Pack Width Master Pack Height Master Pack Length Master Cubic Feet

Certification

UL Standard	Dry
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No

Equivalents

N/A

N/A

845094043522	Incandescent Watts	N/A
N/A	Fluorescent Watts	N/A

ET2 Contemporary Lighting and all designs, logos and images © 2013 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.