

≡ T2	C o n t e m p o r a r y L i g h t i n g™
-------------	---

Product Specifications for E24363-9 IPC		
	Job Name:	Job Type:
		, , , , , , , , , , , , , , , , , , ,
	Quantity:	Comments

E24383-91PC

Illusion 2-Light Wall Sconce

Finish Polished Chrome

Lamping

Number of Bulb(s) 2 **Light Type** Xenon **Bulb Type** G9 Max Bulb Wattage 60 Max Fixture Wattage 120 **Rated Life** ±2,000 Hours **Rated Lumens** ±1,600 **Color Temp** ±2,900 K Bulb(s) Included Yes Light Up/Down N/A **Beam Spread** N/A N/A **Photo Cell Included** N/A

Glass/Shade Bubble

No

Other

UPC Code

Material

Standard Dimmer

Measurements Width N/A 14.50" Height Length 8.00" Extension 4.00" **Back Plate Width** N/A **Back Plate Height** N/A HCO 5.00" Min Overall Height N/A **Max Overall Height** N/A Hanging Weight 2.47 lb(s) **Height Adjustable** N/A Slope N/A Chain Length N/A Wire Length N/A **Canopy Width** Canopy Height Canopy Length N/A

Product Category

Wall Sconce

Shipping **Carton Weight** 3.79 lb(s) Carton Width 10.50" **Carton Height** 7.25" **Carton Length** 14.50" **Carton Cubic Feet** N/A **Master Pack Master Pack Weight** N/A **Master Pack Width** N/A **Master Pack Height** N/A **Master Pack Length** N/A Master Cubic Feet N/A **UPS Shippable** Yes

Certification

Dimmable

Ballast/Driver/Transformer

Safety Rating Dry **Energy Star** No CA Title 24 No CA Title 20 No **ADA** Yes

Equivalents

845094049678

Steel

N/A **Incandescent Watts Fluorescent Watts** N/A

ET2 Contemporary Lighting and all designs, logos and images © 2014 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.