

Product Specifications	for	E94641-1	13SN
------------------------	-----	----------	------

Job Name:	Job Type:
Quantity:	Comments



## E94641-113SN

White Cirrus 3-Light RapidJack Pendant and Canopy

**Finish** Satin Nickel

Lamping

Number of Bulb(s) 3 **Light Type** Xenon **Bulb Type** 12V G4 Max Bulb Wattage 35 **Max Fixture Wattage** 105 **Rated Life** ±2,000 Hours **Rated Lumens** ±1,770 **Color Temp** ±2,900 K Bulb(s) Included Yes Light Up/Down **Beam Spread** N/A N/A **Photo Cell Included** N/A Ballast/Driver/Transformer Yes Dimmable Low-Voltage

Glass/Shade White Cirrus

Measurements

Other

**UPC Code** 

Material

Width 11.75" Height 7.00" Length N/A Extension N/A **Back Plate Width** N/A **Back Plate Height** N/A HCO N/A Min Overall Height N/A **Max Overall Height** 128.25" Hanging Weight 2.74 lb(s) **Height Adjustable** Yes Slope N/A Chain Length N/A Wire Length 180.00" **Canopy Width** 11.8" Canopy Height 1.3" Canopy Length

**Product Category** 

Multi-Light Pendant

Shipping

Carton Weight N/A Carton Width N/A **Carton Height** N/A **Carton Length** N/A **Carton Cubic Feet** N/A **Master Pack** 1 **Master Pack Weight** N/A **Master Pack Width** N/A **Master Pack Height** N/A **Master Pack Length** N/A **Master Cubic Feet** N/A **UPS Shippable** Yes

## Certification

Safety Rating	Dry
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No

**Equivalents** 

845094052098

**Incandescent Watts** N/A **Fluorescent Watts** N/A

ET2 Contemporary Lighting and all designs, logos and images © 2014 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.