

Product Specifications for E95104-1

Job Name:	Job Type:
Quantity:	Comments



ADA

E95104-101SN

Elements 3-Light Flush Mount

Finish Glass/Shade **Product Category** Satin Nickel Flush Mount

Lamping		Measurements		Shipping
Number of Bulb(s)	3	Width	20.00"	Carton Weight
Light Type	Fluorescent	Height	6.25"	Carton Width
Bulb Type	GU24	Length	20.00"	Carton Height
Max Bulb Wattage	18	Extension	N/A	Carton Length
Max Fixture Wattage	54	Back Plate Width	N/A	Carton Cubic F
Rated Life	±10,000 Hours	Back Plate Height	N/A	Master Pack
Rated Lumens	±4,065	HCO	N/A	Master Pack W
Color Temp	±2,700 K	Min Overall Height	N/A	Master Pack W
Bulb(s) Included	Yes	Max Overall Height	N/A	Master Pack He
Light Up/Down	N/A	Hanging Weight	11.07 lb(s)	Master Pack Le
Beam Spread	N/A	Height Adjustable	N/A	Master Cubic F
CRI	N/A	Slope	N/A	UPS Shippable
Photo Cell Included	N/A	Chain Length	N/A	
Ballast/Driver/Transformer	No	Wire Length	N/A	
Dimmable	No	Canopy Width	N/A	
		Canopy Height	N/A	
		Canopy Length	N/A	

Jilippilig	
Carton Weight	19.00 lb(s)
Carton Width	23.75'
Carton Height	12.25'
Carton Length	23.75'
Carton Cubic Feet	N/A
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification Other **Equivalents**

No

Safety Rating	Dry UPC Code	845094039426 Incandescent Watts	370
Energy Star	No Material	N/A Fluorescent Watts	N/A
CA Title 24	Yes		
CA Title 20	No		

ET2 Contemporary Lighting and all designs, logos and images © 2014 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.