

Lighting Your Life Since 1970

Product Specifications - 19045FTPC		
Job Name:	Job Type:	
Quantity:	Comments	



19045FTPC

Elle 5-Light Chandelier

Finish Polished Chrome

Lamping

Number of Bulbs	5
Light Type	Xenon
Bulb Type	G9 Frost
Max Bulb Wattage	75
Max Fixture Wattage	375
Rated Life	±2,000 Hours
Rated Lumens	±6,500
Color Temp	±2,900 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

GI	las	-	S	ha	d	e

Frosted

Measuremei	nte
measar eme	,,,,
\A/: al4la	

Width	30.00"
Height	22.00"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	0.00"
Max Overall Height	66.00"
Hanging Weight	22.44 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	180"
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Product Category

Single-Tier Chandelier

Shinning

Snipping	
Carton Weight	26.62 lbs
Carton Width	14"
Carton Height	9"
Carton Length	28"
Carton Cubic Feet	2.17
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

Certification		Other	
Safety Rating	Dry	UPC Code	783209087378
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	N/A

Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.