

Lighting Your Life Since 1970

Product Specifications - 22172SWPC						
Job Name:	Job Type:					
Quantity:	Comments					



22172SWPC

Elan 3-Light Semi-Flush Mount

Finish Polished Chrome

Lamping

Number of Bulbs	3
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	60
Max Fixture Wattage	180
Rated Life	±2,500 Hours
Rated Lumens	±2,016
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

Glas	s/Shade	9
Satin	White	

Canopy Height

Canopy Length

Measurements	
Width	15.75"
Height	14.50"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
НСО	N/A
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	7.30 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A

Product Category

Semi-Flush Mount

Q.	hi	n	n	in	a
J,	ш	μ	יש	ш	9

Shipping	
Carton Weight	10.00 lbs
Carton Width	20"
Carton Height	10"
Carton Length	25"
Carton Cubic Feet	2.98
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

,	е	rt	ij,	1	С	a	tı	C)	n		

Certification		Other	
Safety Rating	Dry	UPC Code	783209088139
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	N/A

Equivalents

N/A

N/A

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.