

Lighting Your Life Since 1970

Product Specifications - 22243WSPD		
Job Name:	Job Type:	
Quantity:	Comments	



22243WSPD

Fremont 3-Light Invert Bowl Pendant

Finisi	7	
Platinu	ım I	Dusk

9

Lumping	
Number of Bulbs	3
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	100
Max Fixture Wattage	300
Rated Life	±2,500 Hours
Rated Lumens	±3,450
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

Glass/Shade Wilshire

Measurements

Wire Length

Canopy Width

Canopy Height

Canopy Length

Othor

Width

Height	31.50"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	16.58 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	36"

Chinning

25.50"

180"

N/A

N/A

N/A

Product Category

Invert Bowl Pendant

Snipping	
Carton Weight	25.92 lbs
Carton Width	27'
Carton Height	15'
Carton Length	28'
Carton Cubic Feet	6.45
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

Certification		Other	
Safety Rating	Dry	UPC Code	783209059696
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	Yes
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	Steel

Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.