

## Lighting Your Life Since 1970

Product Specifications - 23035SWSN			
Job Name:	Job Type:		
Quantity:	Comments		



## 23035SWSN

Orion 5-Light Chandelier

Satin Nickel

Lamping

Lamping	
Number of Bulbs	5
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	100
Max Fixture Wattage	500
Rated Life	±2,500 Hours
Rated Lumens	±5,750
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

Glas	s/Shade
Satin	White

Measurements	
Width	29.00"
Height	26.50"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	9.44 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	36"
Wire Length	180"
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

## **Product Category**

Single-Tier Chandelier

Q.	hi	n	n	in	a
J	ш	μ	P	ш	y

**Equivalents** 

Snipping	
Carton Weight	20.77 lbs
Carton Width	26
Carton Height	27
Carton Length	27
Carton Cubic Feet	10.76
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Oversize

N/A N/A

Certification	Other

Safety Rating	Dry	UPC Code	783209083998	Incandescent Watts
Energy Star	No	Shades Included	N/A	Fluorescent Watts
CA Title 24	No	Crystals Included	N/A	
CA Title 20	No	Diffuser Included	N/A	
ADA	No	Conversion Kit	N/A	
Dark Sky	N/A	Material	N/A	

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.