

Lighting Your Life Since 1970

Product Specifications - 23073CLFTPC				
Job Name:	Job Type:			
Quantity:	Comments			

Equivalents

Incandescent Watts

Fluorescent Watts

N/A

N/A

783209086784

N/A

N/A

N/A

N/A

Metal



Certification

Safety Rating

Energy Star

CA Title 24

CA Title 20

Dark Sky

ADA

23073CLFTPC Silo 3-Light Bath Vanity

Finish Polished Chrome		Glass/Shade Clear/Frosted		Product Category Bath Vanity	
Lamping	2	Measurements	24.00"	Shipping Control Walnut	0.00 lba
Number of Bulbs	3	Width	21.00"	Carton Weight Carton Width	9.26 lbs "11"
Light Type	Xenon	Height	7.50"		8"
Bulb Type	G9 Frost	•	N/A 5"	Carton Height	8 29"
Max Bulb Wattage	50	Extension Back Plate Width		Carton Length Carton Cubic Feet	1.45
Max Fixture Wattage	150		21.00"		1.45
Rated Life	±2,000 Hours	Back Plate Height	5.00"	Master Pack	
Rated Lumens	±3,900	HCO	N/A	Master Pack Weight	N/A
Color Temp	±2,900 K	Min Overall Height	0.00"	Master Pack Width	N/A
Bulb(s)	Included	Max Overall Height	N/A	Master Pack Height	N/A
Light Up/Down	N/A	Hanging Weight	7.28 lbs	Master Pack Length	N/A
Beam Spread	N/A	Height Adjustable	N/A	Master Cubic Feet	N/A
CRI	N/A	Slope	N/A	UPS Shippable	Yes
Photo Cell Included	N/A	Chain Length	N/A		
Ballast/Driver/Transformer	No	Wire Length	N/A		
Dimmable	Standard	Canopy Width	N/A		
		Canopy Height	N/A		
		Canopy Length	N/A		

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Other

Shades Included

Crystals Included

Diffuser Included

Conversion Kit

Material

Damp UPC Code

No

No

No

No

N/A

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.