


## Lighting Your Life Since 1970

Product Specifications - 25002CLSN		
Job Name:	Job Type:	
Quantity:	Comments	



## 25002CLSN

Hi-Bay 1-Light Pendant



**Finish** 

Satin Nickel

Glass/Shade

Clear Halophane

**Product Category** 

Single Pendant

Lamping

Number of Bulbs	1
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	100
Max Fixture Wattage	100
Rated Life	±2,500 Hours
Rated Lumens	±1,150
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

# Measurements

measurements	
Width	9.00"
Height	18.00"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	0.00"
Max Overall Height	62.00"
Hanging Weight	6.60 lbs
Height Adjustable	N/A
Slope	120°
Chain Length	N/A
Wire Length	72"
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

#### Shippina

Shipping	
Carton Weight	8.80 lbs
Carton Width	14"
Carton Height	13"
Carton Length	25"
Carton Cubic Feet	2.64
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification	Other
Safety Rating Dry	<b>UPC Code</b> 783209093676
Energy Star No	Shades Included N/A
CA Title 24 No	Crystals Included N/A
CA Title 20 No	Diffuser Included N/A
<b>ADA</b> No	Conversion Kit N/A
Dark Sky N/A	Material Metal

### **Equivalents**

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.