

### Lighting Your Life Since 1970

Product Specifications - 25029MSKPN			
Job Name:	Job Type:		
Quantity:	Comments		



#### 25029MSKPN

Mini Hi-Bay 1-Light Pendant

*Finish*Polished Nickel

Lamping

# - Olloned Worker

Lamping	
Number of Bulbs	1
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	60
Max Fixture Wattage	60
Rated Life	
Rated Lumens	±0
Color Temp	
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	N/A

#### **Glass/Shade** Mirror Smoke

#### Measurements

Width	8.75"
Height	9.25"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
НСО	N/A
Min Overall Height	0.00"
Max Overall Height	68.50"
Hanging Weight	4.60 lbs
Height Adjustable	N/A
Slope	120°
Chain Length	N/A
Wire Length	78"
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

## **Product Category**

Single Pendant

# Shipping

Shipping	
Carton Weight	6.25 lbs
Carton Width	13"
Carton Height	15"
Carton Length	13"
Carton Cubic Feet	1.31
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

# Certification

Safety Rating	Dry	UPC Code	783209010604
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	N/A

Other

#### **Equivalents**

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.