

Lighting Your Life Since 1970

Product Specifications - 25060SN/BUI				
Job Name:	Job Type:			

Comments

210

Finish

Satin Nickel

Lamping

Light Type

**Bulb Type** 

Rated Life

Color Temp

Bulb(s)

CRI

**Rated Lumens** 

Light Up/Down

**Photo Cell Included** 

Ballast/Driver/Transformer

**Beam Spread** 

Dimmable

Number of Bulbs

Max Bulb Wattage

**Max Fixture Wattage** 

25060SN/BUI Mini Hi-Bay 1-Light Wall Sconce W/Bulb

Quantity:

## Glass/Shade

## Measurements Width 8.0 1 Incandescent Height 7.2 MB Length Ν Extension 60 1 **Back Plate Width** 60 6.0 **Back Plate Height** 6.0 нсо ±0 N Min Overall Height N Included Max Overall Height N N/A Hanging Weight 3.60 II Height Adjustable N/A N N/A Slope N N/A **Chain Length** N No Wire Length N N/A Canopy Width **Canopy Height** N/A **Canopy Length**

## Product Category Wall Sconce

	Chinning	
	Shipping	
00"	Carton Weight	3.60 lbs
25"	Carton Width	13"
A/A	Carton Height	10"
10"	Carton Length	13"
00"	Carton Cubic Feet	0.86
00"	Master Pack	1
J/A	Master Pack Weight	N/A
۸/A	Master Pack Width	N/A
J/A	Master Pack Height	N/A
lbs	Master Pack Length	N/A
A/A	Master Cubic Feet	N/A
J/A	UPS Shippable	Yes
J/A		
J/A		

Certification		Other		Equivalents	
Safety Rating	Dry	UPC Code	783209020054	Incandescent Watts	N/A
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	No	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	N/A		
Dark Sky	N/A	Material	Metal		

Maxim Lighting International and all designs, logos and images © 2014 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.