



Lighting Your Life Since 1970

## Product Specifications - 31006CU

Job Name:	Job Type:
Quantity:	Comments:



### 31006CU Richmond 9-Light Chandelier

**Finish**  
Colonial Umber

**Glass/Shade**

**Product Category**  
Multi-Tier Chandelier

#### Lamping

Number of Bulbs	9
Light Type	Incandescent
Bulb Type	CA
Max Bulb Wattage	60
Max Fixture Wattage	540
Rated Life	±1,500 Hours
Rated Lumens	±6,048
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard Dimmer

#### Measurements

Width	37.50"
Height	44.00"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	39.59 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	72"
Wire Length	180"
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

#### Shipping

Carton Weight	52.80 lbs
Carton Width	15"
Carton Height	34"
Carton Length	38"
Carton Cubic Feet	10.90
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Oversize

#### Certification

Safety Rating	Dry
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No
Dark Sky	N/A

#### Other

UPC Code	783209054882
Shades Included	Optional
Crystals Included	Optional
Diffuser Included	N/A
Conversion Kit	N/A
Material	Steel

#### Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.