


Lighting Your Life Since 1970

	Product Specifications - 39883BCBZ		
Job Name:		Job Type:	
	Quantity:	Comments	



39883BCBZ **Glimmer 8-Light Pendant**



Finish Bronze

amping		1
lumber of Bulbs	8	١

Light Type Xenon **Bulb Type** G9 Max Bulb Wattage 40 Max Fixture Wattage **Rated Life** ±2,000 Hours **Rated Lumens** ±4,000 Color Temp ±2,900 K Bulb(s) Included Light Up/Down N/A **Beam Spread** N/A CRI N/A **Photo Cell Included** N/A Ballast/Driver/Transformer No Dimmable Standard

Glass/Shade Beveled Crystal

M	ea.	SI	ire	m	٥r	nts

Othor

Width	10.00"
Height	36.50"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
НСО	N/A
Min Overall Height	0.00"
Max Overall Height	77.00"
Hanging Weight	14.50 lbs
Height Adjustable	N/A
Slope	120°
Chain Length	N/A
Wire Length	180"
Canopy Width	5.11"
Canopy Height	0.98"
Canopy Length	5.11"

Product Category

Single Pendant

Shinning

Jilippilig	
Carton Weight	16.28 lbs
Carton Width	14"
Carton Height	13"
Carton Length	14"
Carton Cubic Feet	1.41
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Cortification

Certification	Other
Safety Rating	Dry UPC Code
Energy Star	No Shades Included
CA Title 24	No Crystals Included
CA Title 20	No Diffuser Included
ADA	No Conversion Kit
Dark Sky	N/A Material

Equivalents

783209093393

N/A

Yes

N/A

N/A N/A

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.