

Lighting Your Life Since 1970

Glass/Shade

Canopy Length

	Product Specifications - 40129CDOB					
ĺ	Job Name:	Job Type:				
ĺ	Quantity:	Comments				

Product Category

N/A



Finish

40129CDOB Newbury 2-Light Outdoor Ceiling Mount

1 1111311		Glass/Silaue		r roduct category	
Oriental Bronze		Seedy		Outdoor Ceiling Mount	
Lamping		Measurements		Shipping	
Number of Bulbs	2	Width	10.50"	Carton Weight	9.00 lbs
Light Type	Incandescent	Height	6.00"	Carton Width	14"
Bulb Type	MB	Length	N/A	Carton Height	11"
Max Bulb Wattage	60	Extension	N/A	Carton Length	14"
Max Fixture Wattage	120	Back Plate Width	N/A	Carton Cubic Feet	1.27
Rated Life	±2,500 Hours	Back Plate Height	N/A	Master Pack	1
Rated Lumens	±1,344	HCO	N/A	Master Pack Weight	N/A
Color Temp	±2,700 K	Min Overall Height	0.00"	Master Pack Width	N/A
Bulb(s)	Not Included	Max Overall Height	N/A	Master Pack Height	N/A
Light Up/Down	N/A	Hanging Weight	8.16 lbs	Master Pack Length	N/A
Beam Spread	N/A	Height Adjustable	N/A	Master Cubic Feet	N/A
CRI	N/A	Slope	N/A	UPS Shippable	Yes
Photo Cell Included	N/A	Chain Length	N/A		
Ballast/Driver/Transformer	No	Wire Length	N/A		
Dimmable	Standard	Canopy Width	N/A		
		Canopy Height	N/A		

Certification		Other		Equivalents	
Safety Rating	Damp	UPC Code	783209065284	Incandescent Watts	N/A
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	No	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	N/A		
Dark Sky	N/A	Material	Vivex		

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.