

Lighting Your Life Since 1970

Product Specifications - 40210WGET	
Job Name:	Job Type:
Quantity:	Comments



40210WGET

Whittier VX 3-Light Outdoor Hanging Lantern



Finish Earth Tone

Lam	рι	ng	1
Mirron	h.	~ -	٠.

Number of Bulbs	3
Light Type	Incandescent
Bulb Type	CA
Max Bulb Wattage	60
Max Fixture Wattage	180
Rated Life	±1,500 Hours
Rated Lumens	±2,016
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard Dimmer

Glass/Shade

Water Glass

	urem	

Width	10.00"
Height	21.00"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	6.60 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	72"
Wire Length	144"
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Product Category

Outdoor Hanging Lantern

Shinning

Shipping	
Carton Weight	9.75 lbs
Carton Width	14"
Carton Height	14"
Carton Length	25"
Carton Cubic Feet	2.63
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Cartification

Certification	
Safety Rating	Wet l
Energy Star	No \$
CA Title 24	No (
CA Title 20	No I
ADA	No (
Dark Sky	N/A

04	
Other	
UPC Code	783209064119
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	Vive

Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.