

Lighting Your Life Since 1970

Product Specifications - 40467CDSE		
Job Name:	Job Type:	
Quantity:	Comments	



40467CDSE

Knob Hill VX 3-Light Outdoor Hanging Lantern

Finish Sienna

Lamping Number of Bulbs

Light Type Incandescent **Bulb Type** CA Max Bulb Wattage 60 Max Fixture Wattage 180 Rated Life ±1,500 Hours **Rated Lumens** ±2.016 Color Temp ±2,700 K Bulb(s) Not Included Light Up/Down N/A Beam Spread N/A N/A

Glass/Shade

Seedy

3

N/A

No

Standard Dimmer

Measurements

10.00" Width Height 22.00" Length N/A Extension N/A **Back Plate Width** N/A **Back Plate Height** N/A HCO N/A Min Overall Height 0.00" Max Overall Height N/A **Hanging Weight** .26 lbs **Height Adjustable** N/A Slope N/A **Chain Length** 72" Wire Length 144" **Canopy Width** N/A **Canopy Height** N/A

Product Category

Outdoor Hanging Lantern

Shipping

Cilipping	
Carton Weight	10.50 lbs
Carton Width	13"
Carton Height	13"
Carton Length	23"
Carton Cubic Feet	2.28
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

Dimmable

Photo Cell Included

Ballast/Driver/Transformer

Safety Rating **Energy Star** No CA Title 24 CA Title 20 No **ADA** No Dark Sky N/A

Canopy Length

Other Wet UPC Code 783209063303 Shades Included N/A **Crystals Included** N/A Diffuser Included N/A **Conversion Kit** N/A Material Vivex

Equivalents

N/A

Incandescent Watts N/A Fluorescent Watts N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.