

### Lighting Your Life Since 1970

Product Specifications - 5840FTSN			
Job Name:	Job Type:		
Quantity:	Comments		



#### **5840FTSN Essentials 1-Light Flush Mount**

Finis	sh
Satin	Nickel

# Lamping

#### Number of Bulbs 1 **Light Type** Incandescent **Bulb Type** MB Max Bulb Wattage 60 Max Fixture Wattage 60 **Rated Life** ±2,500 Hours **Rated Lumens** ±672 Color Temp ±2,700 K Bulb(s) Not Included Light Up/Down N/A **Beam Spread** N/A CRI N/A **Photo Cell Included** N/A Ballast/Driver/Transformer No Dimmable Standard

## Glass/Shade

#### Frosted

Measurements	
Width	

Height	6.00"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
НСО	N/A
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	2.25 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

#### **Product Category** Flush Mount

11.50"

Shipping	
Carton Weight	3.50 lbs
Carton Width	13'
Carton Height	6'
Carton Length	13'
Carton Cubic Feet	0.63
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

#### Cartification

Certification		Other	
Safety Rating	Dry	UPC Code	783209056619
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	Iron

#### **Equivalents**

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.