



Lighting Your Life Since 1970

Product Specifications - 87201WT		
Job Name:	Job Type:	
Quantity:	Comments	



Low Profile EE 2-Light Flush Mount





Finish White

Lam	ומ	n	g	
NI	1.		_	

Number of Bulbs	1+1
Light Type	Fluorescent
Bulb Type	4-Pin T9 Circline
Max Bulb Wattage	22+32
Max Fixture Wattage	54
Rated Life	11000+15000
Rated Lumens	±3,000
Color Temp	±3,000 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	Yes
Dimmable	No

Glass/Shade

١	Λ	/r	١İ	te

Measurements

Width	14.00"
Height	2.50"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	2.94 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Product Category

Flush Mount

Chinning

Snipping	
Carton Weight	3.50 lbs
Carton Width	15"
Carton Height	5"
Carton Length	16"
Carton Cubic Feet	0.65
Master Pack	6
Master Pack Weight	23.15 lbs
Master Pack Width	16.14"
Master Pack Height	16.34"
Master Pack Length	29.13"
Master Cubic Feet	4.45
UPS Shippable	Yes

Certification

Safety Rating	Damp
Energy Star	No
CA Title 24	Yes
CA Title 20	No
ADA	No
Dark Sky	N/A

Other	
UPC Code	783209031883
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	Stee

Equivalents

Incandescent Watts	273
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.