



Lighting Your Life Since 1970

Product Specifications - 87920RP

Job Name:	Job Type:
Quantity:	Comments:



87920RP

Flush Mount EE 1-Light Outdoor
Ceiling Mount



ENERGY STAR
CERTIFIED

Finish

Rust Patina

Glass/Shade

Frosted

Product Category

Outdoor Ceiling Mount

Lamping

Number of Bulbs	1
Light Type	Fluorescent
Bulb Type	GU24
Max Bulb Wattage	13
Max Fixture Wattage	13
Rated Life	±10,000 Hours
Rated Lumens	±900
Color Temp	±2,700 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	81-82
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	No

Measurements

Width	11.50"
Height	4.50"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	3.12 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Shipping

Carton Weight	4.33 lbs
Carton Width	12"
Carton Height	7"
Carton Length	12"
Carton Cubic Feet	0.57
Master Pack	6
Master Pack Weight	25.96 lbs
Master Pack Width	24.40"
Master Pack Height	22.83"
Master Pack Length	12.60"
Master Cubic Feet	4.06
UPS Shippable	Yes

Certification

Safety Rating	Damp
Energy Star	Yes
CA Title 24	Yes
CA Title 20	No
ADA	No
Dark Sky	N/A

Other

UPC Code	783209019744
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	Die Cast Aluminum

Equivalents

Incandescent Watts	82
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.