

Lighting Your Life Since 1970

Product Specifications - 9001DWOI			
Job Name:	Job Type:		
Quantity:	Comments		



9001DWOI Essence 1-Light Bath Vanity

FinishOil Rubbed Bronze

Lamping

Number of Bulbs	1
Light Type	Xenon
Bulb Type	G9 Frost
Max Bulb Wattage	60
Max Fixture Wattage	60
Rated Life	±2,000 Hours
Rated Lumens	±800
Color Temp	±2,900 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

Glass/ShadeDusty White

Measurements	
Width	5.25"
Height	5.75"
Length	N/A
Extension	4"
Back Plate Width	4.63"
Back Plate Height	5.75"
HCO	2.75"
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	1.46 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	
Canopy Height	
Canopy Length	N/A

Product CategoryBath Vanity

balli varilly

Shipping	
Carton Weight	2.00 lbs
Carton Width	7"
Carton Height	8"
Carton Length	9"
Carton Cubic Feet	0.28
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

N/A N/A

Cofoty Dating	Dama	LIDC Code	702200000102	Incondoccon
Certification		Other		Equivalents

Safety Rating	Damp	UPC Code	783209900103	Incandescent Watts
Energy Star	No	Shades Included	N/A	Fluorescent Watts
CA Title 24	No	Crystals Included	N/A	
CA Title 20	No	Diffuser Included	N/A	
ADA	Yes	Conversion Kit	N/A	
Dark Sky	N/A	Material	N/A	

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.