


WAFER LED | SURFACE MOUNT

58710 / 58711 / 58810 / 58712 / 58713 / 58812 / 57714 / 58715 / 58814 / 58736 / 58737 / 58780 / 58784

Job Name : _____
 Job Type : _____
 Quantity : _____
 Comments : _____

- Power Source is Patent Pending
- 120 - 277 Input
- Aluminum Construction
- Polycarbonate Lens
- Size Options: 5.5", 7", 9", and 15"
- Thin 0.5" profile from surface
- Suitable for Closets according to NEC Section 410.8 & 410.16
- Finish Options: White (WT) Black (BK) Bronze (BZ) and Satin Nickel (SN)
- Dimmable Options: ELV at 120V and 0-10V
- Easy to install: fits in 3-0 and 4-0 Outlet Box
- Edge Lit LED Technology creates bright and even illumination
- Suitable for Wet Locations above showers and covered ceilings outdoor
- cETLus
- JA8 Title 24 and Energy Star 2.0 Listed



58780WT
7" Empty Shell




58784WTWT
Wafer LED 7" RD w/ 1.5 hours
Emergency Back Up



PRODUCT DESCRIPTION

Wafer was designed for the discriminate consumer who wants the low profile look of recessed without the high cost. Manufactured of die cast aluminum, Wafer brings ultimate heat dissipation to its edge lit technology. Edge lighting gives very even light distribution while dispersing heat over a larger area. The result of this is longer LED life and better light diffusion.



Installs into 3-0 or 4-0 junction box with a minimum of 1.5" depth

FINISHES OPTIONS:

- White (WT)
- Bronze (BZ)
- Satin Nickel (SN)
- Black (BK)



MATERIAL:

Aluminum Construction
Polycarbonate Lens

AVAILABLE SIZES:

5.5" | 7" | 9" | 15"

RATINGS:

cETLus
Wet Location
Energy Star
Title 24 JA8 compliant
ADA
Dimmable:
Closets Rated: 410.8 & 410.16



ADDITIONAL:

RATED LIFE: 50,000 Hours
OPERATING TEMP: -20° C (-4°), 40°C (104°F)
PHOTOMETRIC: Report Found Online

Always consult a qualified electrician before installing any lighting product